

previous revision date : 2023/03/06

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : LHM PLUS
UFI : MN5X-T8H2-V00C-JRUX

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Formulation additives, lubricants and greases - Industrial General use of lubricants and greases in vehicles or machinery - Industrial General use of lubricants and greases in vehicles or machinery - Professional Base oil

1.3 Details of the supplier of the safety data sheet

TotalEnergies Lubrifiants
562 Avenue du Parc de L'île
92029 Nanterre Cedex FRANCE
Tél: +33 (0)1 41 35 40 00
Fax: +33 (0)1 41 35 84 71
rm.msds-lubs@totalenergies.com

TotalEnergies Marketing Denmark A/S
Amerika Plads 29
DK - 2100 København Ø
Tel : +45 45813701
sm.nordic-reach@totalenergies.com

Contact

H.S.E

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : Toxicity Center: +354 543 2222

Supplier

Telephone number : Emergency phone: +44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Asp. Tox. 1, H304
Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

For more details about adverse physical, human health and environmental effects, see sections 9 to 12.

2.2 Label elements

Hazard pictograms :



Signal word :

Danger

Hazard statements :

H304 - May be fatal if swallowed and enters airways.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

General :

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read carefully and follow all instructions.

Prevention :

P273 - Avoid release to the environment.

Response :

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P331 - Do NOT induce vomiting.

Storage :

Not applicable.

Disposal :

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains :

Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics
Distillates (petroleum), hydrotreated light paraffinic

Supplemental label elements :

Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration $\geq 0,1$ %.

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

Other hazards which do not result in classification : Hazard of slipping on spilled product.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Product/substance	Identifiers	% (w/w)	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	REACH #: 01-2119826592-36 EC: 934-954-2 CAS: 64742-46-7*	≥ 50 - ≤ 75	Asp. Tox. 1, H304	-	[1] [2]
Distillates (petroleum), hydrotreated light paraffinic	REACH #: 01-2119487077-29	≥ 25 - ≤ 50	Asp. Tox. 1, H304	-	[1] [2]

2,6-di-tert-butylphenol	EC: 265-158-7 CAS: 64742-55-8 REACH #: 01-2119490822-33 EC: 204-884-0 CAS: 128-39-2	<1	Skin Irrit. 2, H315 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
tris(methylphenyl) phosphate	REACH #: 01-2119531335-46 EC: 215-548-8 CAS: 1330-78-5	≤0.3	Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.	M [Acute] = 1 M [Chronic] = 1	[1]

Additional information : Mineral oil of petroleum origin. Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

The EC substance definition and related classification & labelling have been developed in the framework of the Regulation (EC) No 1907/2006 (REACH). The related CAS number* is used for the purpose of the international inventories present in section 15 of the SDS.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. The exposed person may need to be kept under medical surveillance for 48 hours.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: irritation dryness cracking
Ingestion	: nausea or vomiting breathing difficulty or shortness of breath chemical pneumonitis

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: carbon monoxide carbon dioxide nitrogen oxides phosphorus oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material.

6.3 Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
See Section 10 for incompatible materials before handling or use.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

- Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.



7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/substance	Exposure limit values
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	Ministry of Welfare, List of Exposure Limits (Iceland, 4/2023) [Olíufoka, steinefnaolíuagnir] TWA 8 hours: 1 mg/m ³ . Form: particulates.
Distillates (petroleum), hydrotreated light paraffinic	Ministry of Welfare, List of Exposure Limits (Iceland, 11/2023) [Olíufoka, steinefnaolíuagnir] TWA 8 hours: 1 mg/m ³ . Form: particulates.

Biological Limit Values (BLV)

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following:
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Advisory OEL : Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)

DNELs/DMELs

Product/substance	Type	Exposure	Value	Population	Effects
Distillates (petroleum), hydrotreated light paraffinic	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
	DNEL	Long term Oral	6.75 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	6.75 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	11.25 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	20.9 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	70.61 mg/m ³	Workers	Systemic
2,6-di-tert-butylphenol	DNEL	Long term Oral	0.02 mg/kg bw/day	General population	Systemic
	DNEL	Long term	0.03 mg/m ³	General	Systemic
tris(methylphenyl) phosphate	DNEL	Long term Oral	0.02 mg/kg bw/day	General population	Systemic
	DNEL	Long term	0.03 mg/m ³	General	Systemic



	DNEL	Inhalation Long term Dermal	0.15 mg/ kg bw/day	population General population Workers	Systemic
	DNEL	Long term Inhalation	0.18 mg/m ³		Systemic
	DNEL	Long term Dermal	0.41 mg/ kg bw/day	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Name	Method Detail
2,6-di-tert-butylphenol	Fresh water	700 ng/l	-
	Marine water	70 ng/l	-
	Fresh water sediment	317 µg/kg dwt	-
	Marine water sediment	31.7 µg/kg dwt	-
	Soil	697 µg/kg dwt	-
	Sewage Treatment Plant	10 mg/l	-
	Secondary Poisoning	60 mg/kg	-
	Fresh water	0.001 mg/l	-
	Marine water	0.001 mg/l	-
	Fresh water sediment	2.05 mg/kg dwt	-
	Marine water sediment	0.205 mg/kg dwt	-
	Soil	1.01 mg/kg dwt	-
	Sewage Treatment Plant	100 mg/l	-
	Secondary Poisoning	0.65 mg/kg	-
tris(methylphenyl) phosphate			

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : ☒ safety glasses with side-shields, EN 166.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Hydrocarbon-proof gloves
nitrile rubber
Fluorinated rubber

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

In case of prolonged contact with the product, it is recommended to wear gloves complying with ISO 21420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical

	characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency
Body protection	: ☒ Wear work clothing with long sleeves. Non-skid safety shoes or boots
Respiratory protection	: ☒ Ensure adequate ventilation and check that a safe, breathable atmosphere is present before entry into confined spaces. In case of inadequate ventilation wear respiratory protection: Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid.
Color	: Fluorescent yellowish-green
Odor	: Characteristic.
pH	: Not applicable. Product is non-soluble (in water).
Melting point/freezing point	: Technically not possible to measure
Initial boiling point and boiling range	: >316°C [ISO 3405]
Flash point	: ☒ Open cup: 105°C [ASTM D 92]
Flammability	: ☒ Non-flammable.
Lower and upper explosion limit	: Lower: 7% Upper: 9%
Vapor pressure	: ☒ 0.01 kPa [room temperature] Not applicable. [50°C]
Vapor density	: >2 [Air = 1]
Relative density	: 0.831 to 0.841 [ISO EN 3675]
Density	: 0.831 to 0.841 g/cm ³ [15°C] [ISO EN 3675]
Solubility(ies)	:

Media	Result
water	Not soluble

Miscible with water	: No.
Partition coefficient: n-octanol/ water	: Not applicable.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not applicable.
Viscosity	: ☒ Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): 18 mm ² /s [ISO 3104]

Particle characteristics

Median particle size	: Not applicable.
-----------------------------	-------------------

9.2 Other information

Pour point : -62°C (-79.6°F)

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.

10.5 Incompatible materials : Strong oxidizing agents

10.6 Hazardous decomposition products : ☒ Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
☒ Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	LC50 Inhalation Dusts and mists	Rat - Male, Female	>5266 mg/m ³	4 hours	OECD 403 Read across
	LD50 Dermal	Rabbit - Male, Female	>3160 mg/kg	-	OECD 402 Read across
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	OECD 401 Read across
Distillates (petroleum), hydrotreated light paraffinic	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 420
2,6-di-tert-butylphenol	LD50 Dermal	Rabbit	>5000 mg/kg	-	-
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	OECD 401 401
	LC50 Inhalation Vapor	Rat	11.1 mg/l	1 hours	-
tris(methylphenyl) phosphate	LD50 Dermal	Rabbit	>10000 mg/kg	-	-
	LD50 Oral	Rat	3 g/kg	-	-
	LD50 Oral	Rat	20000 mg/kg	-	-

Acute toxicity estimates

Product/substance	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
☒ tris(methylphenyl) phosphate	3000	N/A	N/A	N/A	N/A

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Product/substance	Result	Species	Score	Exposure	Test
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	Eyes - Edema of the conjunctivae	Rabbit	0.3	24 hours	OECD 405 Read across
	Skin - Erythema/Eschar	Rabbit	0.3	-	404 Read across
2,6-di-tert-butylphenol	Eyes - Cornea opacity	Rabbit	0	-	OECD 405 405
	Skin - Moderate irritant	Rat	-	4 hours 0.5 MI	OECD 404 404
tris(methylphenyl) phosphate	Skin - Mild irritant	Rabbit	-	500 mg	-

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Sensitization

Product/substance	Route of exposure	Species	Result
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	skin	Guinea pig	Not sensitizing
2,6-di-tert-butylphenol	skin	Guinea pig	Not sensitizing

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Product/substance	Test	Experiment	Result
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	OECD 471 Read across	Experiment: In vitro Subject: Bacteria	Negative
	OECD 473 Read across	Experiment: In vitro Subject: Mammalian-Animal	Negative
	OECD 476 Read across	Experiment: In vitro Subject: Mammalian-Animal	Negative
	OECD 474 Read across	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative
	OECD 475 Read across	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative
	OECD 483 Read across	Experiment: In vivo Subject: Mammalian-Animal Cell: Germ	Negative
2,6-di-tert-butylphenol	OECD 471 471	Experiment: In vitro Subject: Bacteria	Negative
	OECD 473	Experiment: In vitro Subject: Mammalian-Animal Cell: Somatic	Negative
	OECD 476	Experiment: In vitro Subject: Mammalian-Animal Cell: Somatic	Negative



Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Product/substance	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
2,6-di-tert-butylphenol	-	Negative	Negative	Rat - Male, Female	Oral	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Conclusion/Summary : Based on available data, the classification criteria are not met.

Aspiration hazard

Product/substance	Result
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated light paraffinic	ASPIRATION HAZARD - Category 1

Conclusion/Summary : Based on available data, the classification criteria are met.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : Defatting to the skin. May cause skin dryness and irritation.
Ingestion : May be fatal if swallowed and enters airways.
☑ Chemical pneumonitis.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : ☑ irritation
dryness
cracking
Ingestion : ☑ nausea or vomiting
☑ breathing difficulty or shortness of breath

Delayed and immediate effects and also chronic effects from short and long term exposure**Short term exposure**

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Product/substance	Result	Species	Dose	Exposure
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	Sub-chronic NOAEL Oral	Rat - Male, Female	>5000 mg/kg	13 weeks; 7 days per week
	Sub-acute NOAEL Inhalation Vapor	Rat - Male, Female	>10400 mg/m ³	90 days; 5 days per week
2,6-di-tert-butylphenol	Sub-chronic NOAEL Oral	Rat - Male, Female	100 mg/kg NOAEL	days

Conclusion/Summary : Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

Harmful to aquatic life with long lasting effects.

12.1 Toxicity

Product/substance	Result	Species	Exposure	Test
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	Acute EC50 10000 mg/l	Algae - <i>Skeletonema costatum</i>	72 hours	ISO 10253
	Acute EC50 3193 mg/l	Daphnia - <i>Acartia tonsa</i>	48 hours	ISO 14669
	Acute LC50 1028 mg/l	Fish	96 hours	-
	Chronic NOELR >1000 mg/l	Daphnia - <i>Daphnia Magna</i>	21 days	OECD 211
	Chronic NOELR >1000 mg/l	Fish - <i>Oncorhynchus mykiss</i>	28 days	-
Distillates (petroleum), hydrotreated light paraffinic	Acute EC50 >100 mg/l	Algae - <i>Pseudokirchnerella subcapitata</i>	48 hours	OECD 201
	Acute EC50 >10000 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours	OECD 202
	Chronic NOEL 10 mg/l	Daphnia - <i>Daphnia magna</i>	21 days	OECD 211
	Chronic NOEL >1000 mg/l	Fish - <i>Oncorhynchus mykiss</i>	21 days	-
2,6-di-tert-butylphenol	Acute EC50 1.2 mg/l	Algae	72 hours	-
	Acute EC50 0.45 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours	-
	Acute LC50 1 mg/l	Fish	96 hours	-
	Chronic NOEC 0.035 mg/l	Daphnia - <i>Daphnia magna</i>	21 days	-
	Chronic NOEC 0.3 mg/l	Fish	28 days	-
tris(methylphenyl) phosphate	Acute EC50 290 µg/l Fresh	Algae - <i>Stephanodiscus</i>	96 hours	-

water	<i>hantzschii</i> - Exponential growth phase		
Acute EC50 0.146 mg/l	Daphnia	48 hours	OECD 202
Acute EC50 170 µg/l Fresh water	Fish - <i>Gasterosteus aculeatus</i>	96 hours	-
Acute EC50 1000 mg/l	Micro-organism	3 hours	-
Acute LC50 0.6 mg/l	Fish	96 hours	-
Chronic NOEC 0.1 mg/l	Daphnia - <i>Daphnia magna</i>	21 days	-

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Product/substance	Test	Result	Dose	Inoculum
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	OECD 306	74 % - Readily - 28 days	-	-

Conclusion/Summary : Not available.

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	-	-	Readily
2,6-di-tert-butylphenol	-	-	Not readily
tris(methylphenyl) phosphate	-	-	Inherent

12.3 Bioaccumulative potential

Product/substance	LogK _{ow}	BCF	Potential
2,6-di-tert-butylphenol	4.48	660	High
tris(methylphenyl) phosphate	5.93	794.33	High

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

Mobility in soil : Given its physical and chemical characteristics, the product generally shows low soil mobility The product is insoluble and floats on water Loss by evaporation is limited

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration >= 0,1 %.

12.6 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Should not be released into the environment.

Hazardous waste : Yes.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 13 01 10*

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ICAO/IATA
14.1 UN number or ID number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,6-di-tert-butylphenol)	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Additional information

ADN : The product is only regulated as a dangerous good when transported in tank vessels.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Labeling : Not applicable.

Other EU regulations

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

DIRECTIVE 2008/68/EC related on the inland transport of dangerous goods

Industrial emissions : Not listed

(integrated pollution prevention and control) -
Air

Industrial emissions : Not listed

(integrated pollution prevention and control) -
Water

Explosive precursors : ☒ Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia inventory (AIIIC)	: At least one component is not listed.
Canada inventory (DSL/NDSL)	: At least one component is not listed in DSL but all such components are listed in NDSL.
China inventory (IECSC)	: At least one component is not listed.
Europe inventory (EC)	: All components are listed or exempted.
Japan inventory	: Japan inventory (CSCL) : At least one component is not listed. Japan inventory (ISHL) : Not determined.
New Zealand Inventory of Chemicals (NZIoC)	: At least one component is not listed.
Philippines inventory (PICCS)	: At least one component is not listed.
Korea inventory (KECI)	: At least one component is not listed.
Taiwan Chemical Substances Inventory (TCSI)	: At least one component is not listed.
Thailand inventory	: Not determined.
Turkey inventory	: Not determined.
United States inventory (TSCA 8b)	: All components are listed or exempted.
Vietnam inventory	: Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

15.2 Chemical Safety Assessment

: This product is classified as H304 «May be fatal if swallowed and enters airways». The risk relates to potential for aspiration. The risk arising from aspiration hazard is solely related to the physico-chemical properties of the substance. The risk can therefore be controlled by implementing risk management measures tailored to this specific hazard. An exposure scenario is not required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ACGIH = American Conference of Governmental Industrial Hygienists
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DNEL = Derived No Effect Level
DMEL = Derived Minimal Effect Level
DMSO = Dimethyl Sulfoxide
EC50 = Half maximal effective concentration
EL50 = median Effective Loading
EUH statement = CLP-specific Hazard statement
HSE = Health, Safety and Environment
IC50 = Half maximal inhibitory concentration
IDHL = Immediately dangerous to life or health
LC50 = Median lethal concentration
LD50 = Median lethal dose

LL50 = median Lethal Loading
 LogKow = logarithm of the octanol/water partition coefficient
 N/A = Not available
 NIOSH = National Institute of Occupational Safety and Health
 NOAEL = No Observed Adverse Effect Level
 NOEC = No Observed Effect Concentration
 NOEL = No Observed Effect Level
 NOELR = No observed Effect Loading Rate
 OECD = Organisation for Economic Co-operation and Development
 OEL = Occupational Exposure Limit
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 QSAR = Quantitative Structure–Activity Relationship
 REL = Recommended Exposure Limit
 STEL = Short Term Exposure Limit
 TLV = Threshold Limit Value
 TWA = Time Weight Average
 VOC = Volatile Organic Compound
 vPvB = Very Persistent and Very Bioaccumulative
 UFI = Unique Formula Identifier
 UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Asp. Tox. 1, H304 Aquatic Chronic 3, H412	Calculation method Calculation method

Full text of abbreviated H statements

H304 H315 H361 H400 H410 H412	May be fatal if swallowed and enters airways. Causes skin irritation. Suspected of damaging fertility or the unborn child. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
--	--

Full text of classifications [CLP/GHS]

Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 3 Asp. Tox. 1 Repr. 2 Skin Irrit. 2	AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 3 ASPIRATION HAZARD - Category 1 TOXIC TO REPRODUCTION - Category 2 SKIN CORROSION/IRRITATION - Category 2
--	---

Date of revision : 2024/10/24
previous revision date : 2023/03/06
Version : 2.01

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture
Code : 32897
Product name : LHM PLUS

Section 1 - Title

Short title of the exposure scenario : Formulation additives, lubricants and greases - Industrial
List of use descriptors : **Identified use name:** Formulation additives, lubricants and greases - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Sector of end use: SU03, SU10
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02

Processes and activities covered by the exposure scenario : Industrial formulation of lubricant additives, lubricants and greases. Includes material transfers, mixing, large and small scale packing, sampling, maintenance.

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 2.Ai-I.v1

Amounts used : Volume manufactured/imported (tonnes/year) : 1.00E+04
Fraction of EU tonnage used in region : 0.1
Fraction of regional tonnage used locally : 0.1

Frequency and duration of use : Emission days (days per year) : 300

Environment factors not influenced by risk management : Local freshwater dilution factor : 10
Local marine water dilution factor : 100

Other operational conditions of use affecting environmental exposure : Negligible wastewater emissions as process operates without water contact.
Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 5.00E-05
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-12
Release fraction to soil from process (after typical onsite RMMs): 0

Technical conditions and measures at process level (source) to prevent release : Common practices vary across sites thus conservative process release estimates used.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil : Treat air emission to provide a typical removal efficiency of (%) : 70
Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system.

Organizational measures to prevent/limit release from site : Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to municipal sewage treatment plant : Estimated substance removal from wastewater via domestic sewage treatment (%): (%) : 0.10
Assumed domestic sewage treatment plant flow (m³/d) : 2.00E+03
Maximum allowable site tonnage (M_{safe}) based on release following total wastewater treatment removal (kg/day) : 210 932

Date of issue/Date of revision : 3/22/2021

19/24

Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

No exposure assessment presented for human health.

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment (environment): : Used ECETOC TRA model.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 2:

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment : Not available.

Health : Not available.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture
Code : 32897
Product name : LHM PLUS

Section 1 - Title

Short title of the exposure scenario : General use of lubricants and greases in vehicles or machinery - Industrial

List of use descriptors : **Identified use name:** General use of lubricants and greases in vehicles or machinery - Industrial
Process Category: PROC01, PROC02, PROC08b, PROC09
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC04, ERC07

Processes and activities covered by the exposure scenario : Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 4.Bi.v1

Amounts used : Volume manufactured/imported (tonnes/year) : 2.63E+03
Fraction of EU tonnage used in region : 0.1
Fraction of regional tonnage used locally : 0.1

Frequency and duration of use : Emission days (days per year) : 300

Environment factors not influenced by risk management : Local freshwater dilution factor : 10
Local marine water dilution factor : 100

Other operational conditions of use affecting environmental exposure : Negligible wastewater emissions as process operates without water contact.
Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 5.00E-05
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-12
Release fraction to soil from process (after typical onsite RMMs): 0

Technical conditions and measures at process level (source) to prevent release : Common practices vary across sites thus conservative process release estimates used.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil : Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system.

Organizational measures to prevent/limit release from site : Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to municipal sewage treatment plant : Estimated substance removal from wastewater via domestic sewage treatment (%): (%) : 0.1
Assumed domestic sewage treatment plant flow (m³/d) : 2.00E+03
Maximum allowable site tonnage (M_{Safe}) based on release following total wastewater treatment removal (kg/day) : 55 500

Date of issue/Date of revision : 3/22/2021

21/24

Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

No exposure assessment presented for human health.

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment (environment): : Used ECETOC TRA model.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 2:

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment : Not available.

Health : Not available.

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

Product definition : Mixture
Code : 32897
Product name : LHM PLUS

Section 1 - Title

Short title of the exposure scenario : General use of lubricants and greases in vehicles or machinery - Professional
List of use descriptors : **Identified use name:** General use of lubricants and greases in vehicles or machinery - Professional
Process Category: PROC01, PROC02, PROC08a, PROC08b, PROC20
Sector of end use: SU22
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC09a, ERC09b

Processes and activities covered by the exposure scenario	: Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.
--	---

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 9.Bp.v1

Amounts used	: Volume manufactured/imported (tonnes/year) : 5.39E+03 Fraction of EU tonnage used in region : 0.1 Fraction of regional tonnage used locally : 0.1
Frequency and duration of use	: Emission days (days per year) : 365
Environment factors not influenced by risk management	: Local freshwater dilution factor : 10 Local marine water dilution factor : 100
Other operational conditions of use affecting environmental exposure	: Negligible wastewater emissions as process operates without water contact. Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 5.00E-04 Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-04 Release fraction to soil from process (after typical onsite RMMs): 1.00E-03
Technical conditions and measures at process level (source) to prevent release	: Common practices vary across sites thus conservative process release estimates used.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil	: Prevent discharge of undissolved substance to or recover from onsite wastewater.
Organizational measures to prevent/limit release from site	: Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
Conditions and measures related to municipal sewage treatment plant	: Estimated substance removal from wastewater via domestic sewage treatment (%): (%) : 0.10 Assumed domestic sewage treatment plant flow (m³/d) : 2.00E+03 Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/day) : 560

Date of issue/Date of revision : 3/22/2021

23/24

Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

No exposure assessment presented for human health.

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment (environment): : Used ECETOC TRA model.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 2:

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment : Not available.

Health : Not available.